

BARI

Revestimiento Monoporosa Rectificado / Wall Tiles Rectified



BARI BLANCO
31,6x90x0,9cm
Butech recomienda junta / Butech recommends joint: Colorstuk Rapid n Blanco B22501001 / 100004294 **G261**

PERFIL BARI BLANCO
1,5x31,6cm **G77**
1,5x90cm **G97**

TECHNICAL SPECS · INFORMACIÓN TÉCNICA

EMBALAJE / PACKING							
FORMATO cm	PZ/CJ	M2/CJ	CJ/PAL	M2/PAL	*KG/CJ	*KG/PAL	Adhesivo
31,6x90cm	4	1,14	57	64,84	18,48	1053,36	Fr-one n
1,5x31,6cm	30	0,28	42	11,94	3,62	151	Fr-one n
1,5x90cm	15	0,41	28	11,34	5,56	155,74	Fr-one n

*valores aproximados. *approximated values.

i PAVIMENTO COMBINABLE: SERIE BARI 59,6x59,6cm · PAG.199
FLOOR TILES COMBINATIONS: BARI SERIES 59,6x59,6cm · PAG.199



BARI BLANCO 31,6x90cm

BARI

Gres Rectificado / Rectified Floor Tiles



BARI BLANCO P-R
59,6x59,6x1,1cm **P1856957 / 100155618** **G347**
Butech recomienda junta / Butech recommends joint: Colorstuk Rapid n Blanco B22501001 / 100004294

TECHNICAL SPECS · INFORMACIÓN TÉCNICA

EMBALAJE / PACKING							
FORMATO cm	PZ/CJ	M2/CJ	CJ/PAL	M2/PAL	*KG/CJ	*KG/PAL	Adhesivo
59,6x59,6cm	4	1,42	32	45,47	35,04	1121,3	one-flex n / maxifluid
10x44,6cm Zócalo	20	0,87	72	62,84	18,79	1352,68	one-flex n
31,6x59,6cm Huella Tec.	2	0,42	48	19,97	11,33	543,84	one-flex n / maxifluid
31,6x59,6cm Huella Tec. Esq.	1	0,21	48	9,98	5,67	271,92	one-flex n / maxifluid

*valores aproximados. *approximated values.

i INTENSIDAD DE TRÁNSITO PEATONAL: TRÁNSITO MODERADO
INTENSITY OF PEDESTRIAN TRANSIT: MODERATE TRANSIT



ZÓCALO	10x44,6cm	
PERSIA BARI BLANCO	P4328113 / 100180414 P8323609 / 100183950	G7 G7



- HUELLA TÉCNICA 31,6x59,6cm

			ESQUINA DERECHA		ESQUINA IZQUIERDA	
PERSIA BARI BLANCO	P9210434 / 100193853 P9210302 / 100169575	G130 G130	P9210440 / 100193949 P9210412 / 100193835	G150 G150	P9210437 / 100193849 P9210406 / 100193845	G150 G150